

# FL 639 - Technical Specifications



## Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Spreader

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 710/40 R 22.5 |
| LI/SS              | 170 B/158 B   |
| LI/SS DRIVE WHEEL  | 158 B         |
| LI/SS FREE ROLLING | 170 B         |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 727             |
| Overall Diameter (mm)      | 1140            |
| Static Loaded Radius (mm)  | 503             |
| Rolling Circumference (mm) | 3492            |
| SRI (mm)                   | 550             |
| Rim Rec                    | AG 24.00        |
| ECE                        | E11-106R-006479 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50 FR      | 2300 | 2650 | 3000 | 3325 | 3650 | 3950 | 4250 | 4560 | 4875 | 5235 | 5600 | 5800 | 6000 |
| 50 DW      | 1650 | 1885 | 2120 | 2345 | 2575 | 2785 | 3000 | 3225 | 3450 | 3725 | 4000 | 4125 | 4250 |

Printed on 4/17/2024 7:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..