



## FL 639 - Data Sheet



### Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Spreader

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>560/45 R 22.5</b>	STANDARD	152 D/163 A8			AG 16.00		543	1076	484	3303	525	TL	E4-106R-000627
<b>600/50 R 22.5</b>	STANDARD	168 B/156 B	156 B	168 B	AG 20.00		611	1172	521	3592	550	TL	E11-106R-006478
<b>600/50 R 22.5</b>	STANDARD	159 D/170 A8			AG 20.00		611	1172	521	3592	550	TL	E4-106R-000802
<b>710/40 R 22.5</b>	STANDARD	170 B/158 B	158 B	170 B	AG 24.00		727	1140	503	3492	550	TL	E11-106R-006479
<b>710/40 R 22.5</b>	STANDARD	161 D/172 A8			AG 24.00		727	1140	503	3492	550	TL	E4-106R-000801
<b>850/40 R 26.5</b>	STANDARD	173 D / 184 A8			AG 28.00		860	1355	599	4122	650	TL	E11-106R-006228

Printed on 4/24/2024 6:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..