



## FL 639 - Data Sheet



### Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Spreader

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>560/45 R 22.5</b>	STANDARD	94034260	152 D/163 A8			AG 16.00		21.4	42.4	19.1	130	TL	E4-106R-000627
<b>600/50 R 22.5</b>	STANDARD	94063239	168 B/156 B	156 B	168 B	AG 20.00		24.1	46.1	20.5	141.4	TL	E11-106R-006478
<b>600/50 R 22.5</b>	STANDARD	94028153	159 D/170 A8			AG 20.00		24.1	46.1	20.5	141.4	TL	E4-106R-000802
<b>710/40 R 22.5</b>	STANDARD	94063246	170 B/158 B	158 B	170 B	AG 24.00		28.6	44.9	19.8	137.5	TL	E11-106R-006479
<b>710/40 R 22.5</b>	STANDARD	94041176	161 D/172 A8			AG 24.00		28.6	44.9	19.8	137.5	TL	E4-106R-000801
<b>850/40 R 26.5</b>	STANDARD	94064779	173 D / 184 A8			AG 28.00		33.9	53.3	23.6	162.3	TL	E11-106R-006228

Printed on 4/24/2024 9:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..