

## FLOTATION 351 - Technical Specifications



### Description

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Version	STANDARD
Type	TL
Tyre Size	66 X 43.00 - 25
LI/SS	170 B

Dimensions US Standard

Usa code	94029495
Ply Rating	16
Section Width (inch)	40.2
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	30.8
Rolling Circumference (inch)	205.2
Rim Rec	36.0 TH
ECE	E11-106R-003346
TRA Code	HF3

Load capacity (lbs)

mph / psi	40
30	13225

Printed on 5/4/2024 5:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..