

## FLOTATION 647 - Data Sheet



### Description

FLOTATION 647 is an implement tire that features best traction on soft soil and grassland. In addition to excellent self-cleaning properties, the specially designed tread pattern provides a wide contact area, which ensures optimized ground pressure and excellent performance on soft soil.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Implement Machinery

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
260/75 - 15.3	STANDARD	119 A8	131 A8	9.00		275	785	363	2380	TL	E11-106R-005838
520/50 - 17	STANDARD	147 B	159 B	AG 16.00		516	965	426	2907	TL	E11-106R-005770
425/70 - 18	STANDARD	143 B	155 B	13.00		435	1065			TL	E11-106R-005851

Printed on 4/25/2024 1:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..