

# FLOTATION 648 - Technical Specifications



## Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Baler • Hay Harvester • Spreader

Version	STANDARD
Type	TL
Tyre Size	700/40 - 22.5
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	166 A8/ 162 B

Dimensions US Standard

Usa code	94006489
Ply Rating	16
Section Width (inch)	27.6
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.1
Rolling Circumference (inch)	139.3
Rim Rec	AG 24.00
ECE	E4-106R-002311

Load capacity (lbs)

mph / psi	26	29	32
5 FR	14550	15480	16360
10 FR	13090	13930	14730
20 FR	11640	12380	13080
25 FR	10390	11060	11680
30 FR	9360	9950	10470
5 DW	10300	10950	11570
10 DW	9260	9840	10420
20 DW	8230	8750	9260
25 DW	7350	7810	8270
30 DW	6610	7030	7390

Printed on 4/30/2024 7:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..