

# FLOTATION 648 - Technical Specifications



## Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Baler • Hay Harvester • Spreader

Version	STANDARD
Type	TL
Tyre Size	750/60 - 30.5
LI/SS DRIVE WHEEL	170 A8/167 B
LI/SS FREE ROLLING	182 A8/179 B

## Dimensions US Standard

Usa code	94006540
Ply Rating	16
Section Width (inch)	29.7
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 24.00
ECE	E4-106R-001552

## Load capacity (lbs)

mph / psi	26	29	32
5 FR	23330	24810	26230
10 FR	21000	22330	23610
20 FR	18660	19850	20990
25 FR	16670	17720	18740
30 FR	15000	15950	17080
5 DW	16470	17510	18520
10 DW	14810	15760	16670
20 DW	13170	14010	14810
25 DW	11760	12510	13230
30 DW	10580	11260	12010

Printed on 4/17/2024 6:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..