

# FLOTATION TR 675 - Technical Specifications



## Description

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

## UM

US Standard

## Construction

✚ BIAS

## Machinery

Agriculture: Implement Machinery • Trailer

Version	DUAL BEAD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	155 A8/151 B
LI/SS FREE ROLLING	168 A8/164 B

## Dimensions US Standard

Usa code	94050147
Ply Rating	20
Section Width (inch)	20.3
Overall Diameter (inch)	46.5
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	141.9
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E11-106R-004395

## Load capacity (lbs)

mph / psi	54	55	58
5 FR	16370	16630	17280
10 FR	14740	14970	15550
20 FR	13090	13300	13820
25 FR	11690	11880	12350
30 FR	10530	10690	11020
5 DW	11580	11770	11960
10 DW	10430	10590	10770
20 DW	9270	9420	9570
25 DW	8280	8410	8540
30 DW	7450	7570	7610

Printed on 5/3/2024 9:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..