

FLOTATION TR 675 - Technical Specifications



Description

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	167 A8/163 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	550
Overall Diameter (mm)	1260
Static Loaded Radius (mm)	547
Rolling Circumference (mm)	3640
Rim Rec	AG 16.00
ECE	E11-106R-004397

Load capacity (Kg)

km/h / bar	2.40	2.60	2.80
10 FR	6970	7310	7630
20 FR	6275	6575	6865
30 FR	5580	5845	6105
40 FR	4980	5220	5450
50 FR	4480	4700	4875
10 DW	4795	5025	5250
20 DW	4315	4525	4725
30 DW	3835	4020	4200
40 DW	3425	3590	3750
50 DW	3085	3230	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/8/2024 5:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..