

FORESTECH - Technical Specifications



Description

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	750/55 - 26.5
LI/SS	177 A8/184 A2

Dimensions International Standard

Ply Rating	20
Section Width (mm)	755
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	680
Rolling Circumference (mm)	4467
Rim Rec	AG 24.00
ECE	E11-106R-003347
TRA Code	LS2

Load capacity (Kg)

km/h / bar	5.00
40	7300
30	7810
10	9000

Printed on 4/23/2024 8:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..