

FS 216 - Technical Specifications



Description

FS 216 has a robust log design with optimum angle and wider width to enhance traction performance for loggers and skidders. It provides excellent cut and chip resistance under the most critical operating conditions and ensures maximum protection against possible damages at any time.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Log Skidder

Version	STEEL BELTED
Type	TL
Tyre Size	28L - 26

Dimensions International Standard

Ply Rating	20
Section Width (mm)	720
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	742
Rolling Circumference (mm)	4912
Rim Rec	DW 25 A ; DW 25 B
ECE	E11-106R-006733
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.80	2.40
10	7300	-
30	-	5150

Printed on 4/24/2024 11:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..