

# HARVESTER SPECIAL - Technical Specifications



## Description

HARVESTER SPECIAL has been specifically designed for harvesters. Its dual –angled lugs provide excellent traction in the fields and a comfortable ride on the road. The special tread design provides a large contact area for extraordinary stability. HARVESTER SPECIAL features a strong casing and a particularly cut-and-chip resistant compound ensuring a longer tire life-cycle.

## UM

International Standard

## Construction

✚ BIAS

## Machinery

Agriculture: Harvester

Version	DUAL BEAD
Type	TL
Tyre Size	23.5 - 25
LI/SS	191 A2

## Dimensions International Standard

Ply Rating	20
Section Width (mm)	615
Overall Diameter (mm)	1665
Static Loaded Radius (mm)	715
Rolling Circumference (mm)	5058
Rim Rec	19.50/2.5
ECE	E11-106R-006954
TRA Code	R1

## Load capacity (Kg)

km/h / bar	3.75
10	10900

Printed on 5/8/2024 1:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..