

# I - 1 - Technical Specifications



## Description

I-1 has been designed for field and road transport as well as for soil tillage operations with implements and trailers. I-1 is a high-speed tire that optimizes travel times so that you can focus on your core business. The special tread design ensures a long service life also in harsh conditions and if there is stubble in the fields.

## UM

International Standard

## Construction

 BIAS

## Machinery

Agriculture: Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	21.5L - 16.1 SL

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	570
Overall Diameter (mm)	1150
Static Loaded Radius (mm)	495
Rolling Circumference (mm)	3510
Rim Rec	W 18 CH
Rim Alt	W 16 CH
TRA Code	I1

## Load capacity (Kg)

km/h / bar	1.70
65	2725

Printed on 5/7/2024 12:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..