



I - 1 - Data Sheet



Description

I-1 has been designed for field and road transport as well as for soil tillage operations with implements and trailers. I-1 is a high-speed tire that optimizes travel times so that you can focus on your core business. The special tread design ensures a long service life also in harsh conditions and if there is stubble in the fields.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

SIZE	Version	TRA Code	LI/SS	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
11L - 14 SL	STANDARD	I1	112 D		8	8.00	8 KB	256	753	333	2206	TL		E11-106R-004268
9.5L - 14 SL	STANDARD	I1	111 D		8	7.00	8 KB	237	745	326	2154	TT		E11-106R-004571
9.5L - 14 SL	STANDARD	I1	111 D		8	7.00	8 KB	237	745	326	2154	TL		E11-106R-004571
11L - 15 SL	STANDARD	I1	118 D		10	8 LB	10 LB	270	770	342	2256	TT		E11-106R-004547
11L - 15 SL	STANDARD	I1	118 D		10	8 LB	10 LB	270	770	342	2256	TL		E11-106R-004547
11L - 15 SL	STANDARD	I1	121 D		12	8 LB	10 LB	270	770	342	2256	TL		E11-106R-003521
11L - 15 SL	STANDARD	I1	113 D		8	8 LB	10 LB	270	770	342	2256	TT		E11-106R-003350
11L - 15 SL	STANDARD	I1	113 D		8	8 LB	10 LB	270	770	342	2256	TL		E11-106R-003350
11L - 15 SL	STUBBLE RESISTANT	I1	113 D		8	8 LB	10 LB	270	770	342	2256	TL		
11L - 15 SL	STUBBLE RESISTANT	I1	121 D		12	8 LB	10 LB	270	770	342	2256	TL		E11-106R-004575
12.5L - 15 SL	STANDARD	I1			10	10 LB		310	820	362	2403	TL		E11-106R-004578
12.5L - 15 SL	STANDARD	I1			12	10 LB		310	820	362	2403	TT		E11-106R-003371
12.5L - 15 SL	STANDARD	I1			12	10 LB		310	820	362	2403	TL		E11-106R-003371
12.5L - 15 SL	STANDARD	I1	119 D		8	10 LB		310	820	362	2403	TT		E11-106R-004577
12.5L - 15 SL	STANDARD	I1	119 D		8	10 LB		310	820	362	2403	TL		E11-106R-004577
12.5L - 15 SL	STANDARD	I1	123 D		10	10 LB		310	820	362	2403	TT		E11-106R-004578
12.5L - 15 SL	STUBBLE RESISTANT	I1			12	10 LB		310	820	362	2403	TL		E11-106R-004580
6.70 - 15 SL	STANDARD	I1	97 D		6	4½ KB	5 KB	172	710	319	2080	TL		E11-106R-003443
6.70 - 15 SL	STANDARD	I1	97 D		6	4½ KB	5 KB	172	710	319	2080	TT		E11-106R-003443
6.70 - 15 SL	STANDARD	I1	102 D		8	4½ KB	5 KB	172	710	319	2080	TT		E11-106R-005266
7.60 - 15 SL	STANDARD	I1	106 D		8	5.50	6 LB	193	734	328	2151	TL		
7.60 - 15 SL	STANDARD	I1	110 D		10	5.50	6 LB	193	734	328	2151	TL		E11-106R-003520
7.60 - 15 SL	STANDARD	I1	100 D		6	5.50	6 LB	193	734	328	2151	TT		
7.60 - 15 SL	STANDARD	I1	106 D		8	5.50	6 LB	193	734	328	2151	TT		
7.60 - 15 SL	STANDARD	I1	110 D		10	5.50	6 LB	193	734	328	2151	TT		E11-106R-003520
9.5L - 15 SL	STANDARD	I1	105 D		6	7.00	8 LB	241	765	340	2242	TT		E11-106R-003444
9.5L - 15 SL	STANDARD	I1	112 D		8	7.00	8 LB	241	765	340	2242	TT		E11-106R-003445
9.5L - 15 SL	STANDARD	I1	112 D		8	7.00	8 LB	241	765	340	2242	TL		E11-106R-003445
9.5L - 15 SL	STANDARD	I1	121 D		12	7.00	8 LB	241	765	340	2242	TL		E11-106R-003370
9.5L - 15 SL	STUBBLE	I1	112		8	7.00	8 LB	241	765	340	2242	TL		E11-106R-

	RESISTANT		D										003363
9.5L - 15 SL	STUBBLE RESISTANT	I1	121 D	12	7.00	8 LB	241	765	340	2242	TL		E11-106R-003383
10.0/75 - 15.3	STANDARD	I1		118 D	12	9.00		270	765		TT		E11-106R-006267
10.0/75 - 15.3	STANDARD			118 D	12	9.00		270	765		TL		E11-106R-006267
11L - 16 SL	STANDARD	I1			8	8 LB	10 LB ; W 8 L	270	795	355	2329	TT	E11-106R-006675
11L - 16 SL	STANDARD	I1			10	8 LB	10 LB ; W 8 L	270	795	355	2329	TT	E11-106R-004286
11L - 16 SL	STANDARD	I1			12	8 LB	10 LB ; W 8 L	270	795	355	2329	TT	E11-106R-004287
12.5L - 16 SL	STANDARD	I1			12	10 LB	W 10 L	310	845	374	2476	TL	E11-106R-004294
12.5L - 16 SL	STANDARD	I1			8	10 LB	W 10 L	310	845	374	2476	TT	E11-106R-005101
12.5L - 16 SL	STANDARD	I1			10	10 LB	W 10 L	310	845	374	2476	TT	E11-106R-004293
12.5L - 16 SL	STANDARD	I1			12	10 LB	W 10 L	310	845	374	2476	TT	E11-106R-004294
12.5L - 16 SL	STUBBLE RESISTANT	I1			14	10 LB	W 10 L	310	845	374	2476	TL	E11-106R-004296
7.50 - 16 SL	SPECIAL	I1			8	5.50 F	6 LB	205	785	350	2300	TT	
7.50 - 16 SL	SPECIAL	I1			10	5.50 F	6 LB	205	785	350	2300	TT	
7.50 - 16 SL	STANDARD	I1			8	5.50 F	6 LB	205	785	350	2300	TT	E11-106R-003522
7.50 - 16 SL	STANDARD	I1			10	5.50 F	6 LB	205	785	350	2300	TT	E11-106R-004278
9.00 - 16 SL	STANDARD	I1			10	6 LB	8 LB ; W 8 L	234	845	374	2476	TL	E11-106R-004642
9.00 - 16 SL	STANDARD	I1			10	6 LB	8 LB ; W 8 L	234	845	374	2476	TT	E11-106R-004642
14L - 16.1 SL	STANDARD	I1			12	W 11 C		360	935	409	2740	TL	E11-106R-004298
14L - 16.1 SL	STANDARD	I1			8	W 11 C		360	935	409	2740	TL	E11-106R-004297
16.5L - 16.1 SL	STANDARD	I1	145 D		14	W 14 C	W 14 CH	435	1025	444	3003	TL	E11-106R-007163
16.5L - 16.1 SL	STANDARD	I1	138 D		10	W 14 C	W 14 CH	435	1025	444	3003	TL	E11-106R-003391
19L - 16.1 SL	STANDARD	I1			10	W 16 C	W 16 CH	490	1100	474	3223	TL	E11-106R-004299
19L - 16.1 SL	STANDARD	I1			14	W 16 C	W 16 CH	490	1100	474	3223	TL	E11-106R-006676
19L - 16.1 SL	STANDARD	I1			12	W 16 C	W 16 CH	490	1100	474	3223	TL	E11-106R-004300
21.5L - 16.1 SL	STANDARD	I1			18	W 18 CH	W 16 CH	570	1150	495	3510	TL	E11-106R-004301
21.5L - 16.1 SL	STANDARD	I1			8	W 18 CH	W 16 CH	570	1150	495	3510	TL	0
21.5L - 16.1 SL	STANDARD	I1			14	W 18 CH	W 16 CH	570	1150	495	3510	TL	E11-106R-006677
21.5L - 16.1 SL	STUBBLE RESISTANT	I1	143 D		8	W 18 CH	W 16 CH	570	1150	495	3510	TL	E11-106R-006859
10.5/80 - 18	STANDARD	I1		135 A8	12	W 9	W 8 ; 9	280	890	417	2679	TT	1
11.25 - 24 SL	STANDARD	I1			8	W 10 H	W 10 ; W 8	325	1171	0	0	TL	E11-106R-004402
9.00 - 24 SL	STUBBLE RESISTANT	I1			8	W 8 H		272	1094	0	0	TL	E11-106R-006674

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..