

## LG SMOOTH - Technical Specifications



### Description

LG SMOOTH is a lawn and garden tire suitable for mowers. While the tire is gentle on the ground, the enhanced design ensures increased durability and eases handling. LG SMOOTH is available in an "aramid-belted" version for users who need strengthened puncture resistance.

### UM

US Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Mower • Small Tractor

Version	ARAMID BELTED
Type	TL
Tyre Size	20 X 10.00 - 10

Dimensions US Standard

Usa code	94013067
Ply Rating	6
Section Width (inch)	9.6
Overall Diameter (inch)	19.7
Static Loaded Radius (inch)	8.8
Rolling Circumference (inch)	57.1
Rim Rec	8.00 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005220

Load capacity (lbs)

mph / psi	32
10	1455

Printed on 5/2/2024 12:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..