

## LOADER SPECIAL - Technical Specifications

### Description

LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.



### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Dozer • Loader

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

## Dimensions International Standard

<b>Ply Rating</b>	32
<b>Overall Width (mm)</b>	686
<b>Overall Diameter (mm)</b>	1815
<b>Static Loaded Radius (mm)</b>	833
<b>Rolling Circumference (mm)</b>	5372
<b>Rim Rec</b>	22.00/3.0
<b>TRA Code</b>	L5

## Load capacity (Kg)

km/h / bar	5.50
10	17000

Printed on 4/17/2024 8:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..