

LOADER SPECIAL - Technical Specifications



Description

LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavyduty rock operations. Optimum traction and exceptional cut resistance will boost productivity.

UM
US Standard

Construction

Machinery

OTR: Dozer • Loader

Version	STEEL BELTED
Туре	TL
Tyre Size	40/65 - 39

Dimensions US Standard

Usa code	94075454
Ply Rating	56
Overall Width (inch)	39.4
Overall Diameter (inch)	94.7
Rim Rec	32.00/4.0
TRA Code	L5

Load capacity (lbs)

mph / psi	105
5	85500

Printed on 5/5/2024 2:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..