

# MAGLIFT EXCAVATOR - Technical Specifications



## Description

MAGLIFT EXCAVATOR has been specifically designed for wheeled excavators in digging, loading and road construction operations. The tire is made of a special tread compound, which ensures excellent cut and chip resistance and an extended tire life-cycle. The aggressive tread design provides a high level of handling comfort combined with excellent lateral traction even under heavy-duty service conditions in addition to top self-cleaning properties. Its reinforced bead structure ensures best grip and eliminates any slippage risk during operations, whilst the special bead shape simplifies mounting operations on the rim. MAGLIFT EXCAVATOR is a puncture-and-maintenance-free tire operators can rely on.

## UM

International Standard

## Construction

◆ SOLID

## Machinery

Industrial: Excavator

Version	STANDARD
Type	
Tyre Size	12.00 - 20

## Dimensions International Standard

Overall Width (mm)	255
Overall Diameter (mm)	1100
Rim Rec	8.00 - 20

## Load capacity (Kg)

km/h / bar	-
Static	9515
10	6865
25	6300

Printed on 4/29/2024 4:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..