

MAGLIFT EXCAVATOR - Data Sheet



Description

MAGLIFT EXCAVATOR has been specifically designed for wheeled excavators in digging, loading and road construction operations. The tire is made of a special tread compound, which ensures excellent cut and chip resistance and an extended tire life-cycle. The aggressive tread design provides a high level of handling comfort combined with excellent lateral traction even under heavy-duty service conditions in addition to top self-cleaning properties. Its reinforced bead structure ensures best grip and eliminates any slippage risk during operations, whilst the special bead shape simplifies mounting operations on the rim. MAGLIFT EXCAVATOR is a puncture-and-maintenance-free tire operators can rely on.

UM

International Standard

Construction

◆ SOLID

Machinery

Industrial: Excavator

SIZE	Version	RIM REC	RIM ALT	OW	OD	Type
10.00 - 20	STANDARD	7.50 - 20		240	1010	
10.00 - 20	STANDARD	8.00 - 20		246	1010	
10.00 - 20	STANDARD	7.00 - 20		240	1010	
12.00 - 20	STANDARD	8.50 - 20		265	1100	
12.00 - 20	STANDARD	8.00 - 20		255	1100	

Printed on 5/14/2024 6:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..