

## MAGLIFT PREMIUM - Technical Specifications



### Description

MAGLIFT PREMIUM is a solid tire specially designed for heavy forklift operations in port, mining or scrap yard applications. The extra deep tread (25% more compared to the standard version) with its aggressive and robust pattern provides outstanding front and lateral traction in addition to excellent steering control. The unique tread compound ensures high cut and chip resistance resulting in an extended tire life-cycle. Additional features are low rolling resistance and a smooth run.

### UM

International Standard

### Construction

◆ SOLID

### Machinery

Industrial: Forklift

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      |           |
| Tyre Size | 7.00 - 12 |

## Dimensions International Standard

|                       |             |
|-----------------------|-------------|
| Section Width (mm)    | 163         |
| Overall Diameter (mm) | 664         |
| Rim Rec               | 5.00 S - 12 |

## Load capacity (Kg)

|                | km/h / bar | -    |
|----------------|------------|------|
| 25 LOAD WHEEL  |            | 2920 |
| 25 STEER WHEEL |            | 2240 |

Printed on 5/7/2024 12:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..