

MAGLIFT RIM GUARD - Data Sheet



Description

MAGLIFT (RIM GUARD) is specially engineered and designed for heavy duty forklifts used in industrial and logistic facilities. Its aggressive and robust tread pattern provide superior forward and lateral traction and excellent steering control. In addition, the wide center rib provides a low rolling resistance. The solid construction of MAGLIFT (RIM GUARD) features a high load capacity and an outstanding comfort, while its specially designed rim guard ensures protection against wheel damage. In addition, this tire shows excellent cut and chip resistance resulting in a longer tire life. MAGLIFT (RIM GUARD) reinforced structure eliminates slippage risk whilst the special bead shape simplifies mounting operations on the rim.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Forklift

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	Type
6.50 - 10	STANDARD	94066285	5.00 F - 10		6.1	22.6	
6.50 - 10	STANDARD	94066308	5.50 F - 10		6.1	22.6	
7.00 - 12	STANDARD	94066292	5.00 S - 12		6.6	25.9	

Printed on 4/30/2024 2:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..