

## MP 570 - Technical Specifications



### Description

MP 570 is an agro-industrial tire, which is suitable for excavators and backhoe loaders. This tire provides good traction and durability, as well as excellent self-cleaning properties in all operating conditions.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Backhoe Loader

Industrial: Backhoe Loader • Excavator • Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

## Dimensions US Standard

Usa code	94038329
Ply Rating	12
Section Width (inch)	13.2
Overall Diameter (inch)	41.3
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	123.2
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022634

## Load capacity (lbs)

	mph / psi	51
	50	4540
	30	5070

Printed on 5/3/2024 9:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..