



PL 801 - Data Sheet



Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Hay Harvester • Rotor Rake / Tedder • Forklift
Industrial: Forklift

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
23 X 5 (23 X 5 (- 13))	STANDARD		6	3.75 P		154	640	TT	
18 X 7 - 8 (180/70 - 8)	STANDARD		14	4.33 R	5.00 F	173	470	TT	
18 X 7 - 8 (180/70 - 8)	STANDARD	121 A8	16	4.33 R	5.00 F	173	470	TT	E11-106R-003642
5.00 - 8	STANDARD		8	3.00 D	3.25 I	135	468	TT	E11-106R-003381
5.00 - 8	STANDARD		10	3.00 D	3.25 I	135	468	TT	
21 X 8 - 9 (200/75 - 9)	STANDARD		16	6.00 E	7.00 E	200	535	TT	
21 X 8 - 9 (200/75 - 9)	STANDARD		14	6.00 E	7.00 E	200	535	TT	E11-106R-003643
6.00 - 9	SPECIAL		10	4.00 E		157	543	TT	
6.00 - 9	STANDARD	A8 114	10	4.00 E		157	543	TT	E11-106R-003564
6.00 - 9	STANDARD		12	4.00 E		157	543	TT	E11-106R-003565
6.50 - 10	STANDARD		10	5.00 F	5.50 F	185	595	TT	E11-106R-003566
7.00 - 12	STANDARD		12	5.00 S		189	692	TT	E11-106R-003567
7.00 - 12	STANDARD		14	5.00 S		189	692	TT	E11-106R-003398
250 - 15 (250/70 - 15)	STANDARD		16	7.50 BD	7.0 ; 7.5	235	745	TT	
250 - 15 (250/70 - 15)	STANDARD		20	7.50 BD	7.0 ; 7.5	235	745	TT	
300 - 15 (315/70 - 15)	STANDARD		18	8.00 BD	8.0	295	840	TT	E11-106R-007161
5.50 - 15	STANDARD		8	4.50 E DT	4.50 E SDC	157	670	TT	
7.00 - 15 (30 X 8 - 15)	STANDARD		14	6.0	5.50 BD ; 5.5	206	775	TT	
7.00 - 15 (29 X 8 - 15)	STANDARD		12	5.5	4.33 R ; 5.0	200	750	TT	
7.00 - 15 (30 X 8 - 15)	STANDARD		12	6.0	5.50 BD ; 5.5	206	775	TT	
7.50 - 15	STANDARD		12	6.0	6.00 S ; 6.5	220	785	TT	
7.50 - 15 (7.50 - 15 (32" OD))	STANDARD		14	6.0	6.00 S ; 6.5	220	814	TT	
7.50 - 15	STANDARD		14	6.0	6.00 S ; 6.5	220	785	TT	
8.15 - 15 (28 X 9 - 15)	STANDARD		12	7.0	7.00 BD	215	720	TT	
8.15 - 15 (28 X 9 - 15)	STANDARD		14	7.0	7.00 BD	215	720	TT	E11-106R-003631
8.25 - 15	STANDARD		12	6.5	6.0 ; 7.0	236	854	TT	
8.25 - 15	STANDARD		14	6.5	6.0 ; 7.0	236	854	TT	E11-106R-003402

Printed on 4/25/2024 9:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..