

POWER TRAX HD (FL) - Technical Specifications



Description

POWER TRAX HD is a premium bias-ply tire that is specially designed for forklift equipment in industrial applications. The deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut, chip and tear resistance suitable for rough and hard concrete surface. The specially designed rim guard ensures protection against flats and wheel damages in the rim flange area.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Forklift

Version	IMPLEMENT
Type	TT
Tyre Size	28 X 12.5 - 15
LI/SS	149 A8

Dimensions International Standard

Ply Rating	24
Section Width (mm)	304
Overall Diameter (mm)	705
Rim Rec	9.75 BD
ECE	E11-106R-003423

Load capacity (Kg)

km/h / bar	10.00
40	3250

Printed on 5/5/2024 11:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..