

PRO RIB F2M - Technical Specifications



Description

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: 2WD Tractor
Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	10.00 - 16 SL
LI/SS	110 A8

Dimensions International Standard

Ply Rating	8
Section Width (mm)	275
Overall Diameter (mm)	894
Static Loaded Radius (mm)	409
Rolling Circumference (mm)	2620
Rim Rec	8 LB
Rim Alt	W 8 L
ECE	E4-106R-002666
TRA Code	F2M

Load capacity (Kg)

km/h / bar	3.00
40	1060

Printed on 4/23/2024 8:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..