

## PRO RIB F2M - Technical Specifications



### Description

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor  
Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	9.5L - 15 SL
LI/SS	102 A8

Dimensions US Standard

Usa code	94020492
Ply Rating	8
Section Width (inch)	9.4
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	14.3
Rolling Circumference (inch)	91.5
Rim Rec	7.00
Rim Alt	8 LB
ECE	E4-106R-002644
TRA Code	F2M

Load capacity (lbs)

mph / psi	48
25	1870

Printed on 5/3/2024 12:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..