

## RIB 713 - Technical Specifications



### Description

RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The steel-belted structure provides excellent puncture resistance and hence increased protection against stub penetration and relative damage, even if running into strong stubble. In addition, "D" speed rating (65 km/h - 40 mph) allows for fast road transfers. RIB 713 is BKT's contribution to maximize both the productivity and efficiency of your farming business

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Implement Machinery

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 280/70 R 15
LI/SS	134 D

Dimensions US Standard

Usa code	94052721
TMPH	1
Section Width (inch)	11
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	92.8
Rim Rec	W 8
ECE	E11-106R-005094
TRA Code	I1

Load capacity (lbs)

mph / psi	12	15	17	20	23	29	35	41	46	52	58	64
From 5 to 40 mph	1710	1950	2230	2470	2700	2940	3140	3460	3740	3970	4400	4675

Printed on 5/6/2024 11:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..