

RIB 775 - Technical Specifications



Description

RIB 775 is a low-section cross-ply tire for transport and soil tillage applications with trailers and implement machinery. It offers great load capacity and a long tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	300/65 - 12
LI/SS FREE ROLLING	116 A8

Dimensions US Standard

Usa code	94011049
Ply Rating	8
Section Width (inch)	12
Overall Diameter (inch)	27
Static Loaded Radius (inch)	12
Rolling Circumference (inch)	79
Rim Rec	9.0
ECE	E11-106R-003582

Load capacity (lbs)

mph / psi	38
5 FR	3860
15 FR	3280
20 FR	3090
25 FR	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 12:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..