



## RIB F3 - Data Sheet



### Description

RIB F3 is a field-oriented tire designed for 2WD tractors in soil tillage and haulage operations. Some sizes are suitable for transport applications using trailers. The RIB F3 tire is the ideal partner for all operations that require a high level of handling. It has been designed with a hard compound to ensure great durability and stubble resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor • Trailer

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	94042227	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	9.6	34.6	15.2	101.3	TT	E11-106R-004658
9.00 - 16	STANDARD	94027781	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	9.6	34.6	15.2	101.3	TT	E11-106R-004592
9.00 - 16	STANDARD	94060016	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	9.6	34.6	15.2	101.3	TL	E11-106R-004592

Printed on 4/13/2024 11:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..