



RIDEMAX IT 696 - Data Sheet



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
240/70 R 16 IND	STANDARD	107A8/107B	W8	W9	244	742	343	2226	350	TL		E11-106R-006942
340/80 R 18 IND	STANDARD	143 A8/138 D	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	343	1001	458	2980	475	TL		E11-106R-002987
360/80 R 20 IND	STANDARD	143D/147A8	11	W 10 ; W 11 ; 12 ; W 12	357	1084	488	3235	525	TL		E11-106R-007845
300/80 R 24 IND (11.2 R 24)	STANDARD	133 A8/128 D	DW 10		295	1090	501	3296	525	TL		E4-106R-002292
340/80 R 24 IND (12.4 R 24)	STANDARD	140 A8/135 D	DW 11	W 10 ; W 12 ; DW 10	343	1154	521	3444	550	TL		E4-106R-002293
360/80 R 24 IND (13.6 R 24)	STANDARD	143 A8/138 D	DW 11	W 12 ; W 10	343	1186	537	3556	575	TL		E11-106R-004753
400/80 R 24 IND (14.9 R 24)	STANDARD	149 A8/144 D	DW 13	W 12 ; W 14 L	404	1250	558	3760	600	TL		E4-106R-002400
420/65 R 24 IND	STANDARD	146 D/151 A8	DW 13 L ; W13	DW 15 L ; DW 14 L	418	1158	530	3483	550	TL	1	E11-106R-005952
440/80 R 24 IND (16.9 R 24)	STANDARD	154 A8/149 D	DW 14 L	DW 15 L ; DW 13	441	1314	590	3939	625	TL		E11-106R-004760
460/65 R 24 IND	STANDARD	151 D/156 A8	DW 14 L	DW 15 L ; DW 13	455	1214	549	3644	600	TL	1	
500/70 R 24 IND	STANDARD	164A8/159D	DW 16 L	DW 15 L ; DW 18 L	503	1310	602	3954	625	TL		E11-106R-007547
500/70 R 24 IND	STANDARD	157 A8/152 D	DW 16 L	DW 15 L ; DW 18 L	503	1310	602	3954	625	TL		E11-106R-007051
400/80 R 28 IND (14.9 R 28)	STANDARD	151 A8/146 D	W 13	W 12 ; W 14 L	404	1352	615	4048	650	TL		E4-106R-002401
440/80 R 28 IND (16.9 R 28)	STANDARD	156 A8/151 D	W 14 L	W 15 L	441	1415	634	4288	675	TL		E4-106R-002299
440/80 R 30 IND (16.9 R 30)	STANDARD	157 A8/153 D	W 14 L	W 15 L	441	1466	668	4456	700	TL		E4-106R-002297
480/80 R 30 IND (18.4 R 30)	STANDARD	162 A8/157 D	W 15 L	W 16 L	479	1530	673	4558	725	TL		E4-106R-002298
440/80 R 34 IND (16.9 R 34)	STANDARD	159 A8/155 D	DW 14 L	DW 15 L ; DW 16 L	441	1567	704	4775	750	TL		E4-106R-002295
480/80 R 34 IND (18.4 R 34)	STANDARD	164 A8/159 D	W 15 L	W 16 L	479	1632	728	4894	775	TL		E4-106R-002296
480/80 R 38 IND (18.4 R 38)	STANDARD	166 A8/161 D	W 15 L	W 16 L	479	1733	780	5213	825	TL		E11-106R-004075
540/80 R 38 IND	STANDARD	172 A8/167 D	W 18 L	W 16 L	550	1829	833	5537	875	TL		E11-106R-004077
540/80 R 42 IND	STANDARD	168 D/173 A8	W 18 L	W 16 L	560	1931	879	5875	925	TL		E11-106R-005714

Printed on 4/23/2024 11:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..