



RM 500 - Data Sheet



Description

RM 500 is a steel-belted radial tire suitable for harvester implement applications. It features a strong casing and a special tread design providing high load capacity and particular cut-and-chip resistance. Thanks to its large footprint, RM 500 ensures great pressure distribution on the ground with reduced soil compaction in addition to excellent traction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
500/70 R 24	STEEL BELTED	167 A8 / 155 A8	155 A8	167 A8	W 16 L	W 15 L	502	1310	572	3907	625	TL	E11-106R-005989
500/85 R 24	STEEL BELTED	182 A8 / 170 A8	170 A8	182 A8	W 16 L	W 15 L	520	1460	622	4382	700	TL	E11-106R-005991
500/80 R 28	STEEL BELTED	176 A8 / 164 A8	164 A8	176 A8	W 16 L	W 15 L	503	1495	635	4355	700	TL	E11-106R-005990
600/65 R 28	STEEL BELTED	177A8/165A8	165 A8	177 A8	W 18 L	W 20 L	590	1486	640	4340	700	TL	E11-106R-007699
600/65 R 28	STEEL BELTED	168 A8 / 156 A8	156 A8	168 A8	W 18 L	W 20 L	590	1486	640	4340	700	TL	E11-106R-005993
500/85 R 30	STEEL BELTED	176A8/164A8	164 A8	176 A8	W 16 L	W 15 L	535	1610	674	4745	775	TL	E11-106R-006398

Printed on 4/13/2024 1:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..