

RM 500 - Data Sheet



Description

RM 500 is a steel-belted radial tire suitable for harvester implement applications. It features a strong casing and a special tread design providing high load capacity and particular cut-and-chip resistance. Thanks to its large footprint, RM 500 ensures great pressure distribution on the ground with reduced soil compaction in addition to excellent traction.

UM

US Standard

Construction



₩ RADIAL

Machinery

Agriculture: Harvester

| SIZE | Version | USACode | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | Туре | ECE |
|----------------|-----------------|----------|--------------------|----------------------|-----------------------|------------|------------|------|------|------|-------|------|-------------------------|
| 500/70 R 24 | STEEL BELTED | 94062430 | 167 A8 / 155 A8 | 155 A8 | 167 A8 | W 16 L | W 15 L | 19.8 | 51.6 | 22.5 | 153.8 | TL | E11- 106R- 005989 |
| 500/85 R 24 | STEEL BELTED | 94061570 | 182 A8 / 170 A8 | 170 A8 | 182 A8 | W 16 L | W 15 L | 20.5 | 57.5 | 24.5 | 172.5 | TL | E11- 106R- 005991 |
| 500/80 R 28 | STEEL BELTED | 94063697 | 176 A8 / 164 A8 | 164 A8 | 176 A8 | W 16 L | W 15 L | 19.8 | 58.9 | 25 | 171.5 | TL | E11- 106R- 005990 |
| 600/65 R 28 | STEEL BELTED | 94070961 | 177A8/165A8 | 165 A8 | 177 A8 | W 18 L | W 20 L | 23.2 | 58.5 | 25.2 | 170.9 | TL | E11- 106R- 007699 |
| 600/65 R 28 | STEEL BELTED | 94063666 | 168 A8 / 156 A8 | 156 A8 | 168 A8 | W 18 L | W 20 L | 23.2 | 58.5 | 25.2 | 170.9 | TL | E11- 106R- 005993 |
| 500/85 R 30 | STEEL BELTED | 94065097 | 176A8/164A8 | 164 A8 | 176 A8 | W 16 L | W 15 L | 21.1 | 63.4 | 26.5 | 186.8 | TL | E11- 106R- 006398 |

Printed on 4/20/2024 12:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..