

## ROCK GRIP L4 - Technical Specifications



### Description

ROCK GRIP (L-4) is a bias-ply tire designed for wheel loader operations in severe loading service and on rough ground conditions. Its specially designed, cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The (L-4) tread depth provides an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Dozer • Loader

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

## Dimensions International Standard

<b>Ply Rating</b>	32
<b>Overall Width (mm)</b>	375
<b>Overall Diameter (mm)</b>	1410
<b>Static Loaded Radius (mm)</b>	649
<b>Rolling Circumference (mm)</b>	4173
<b>Rim Rec</b>	10.00/1.5
<b>TRA Code</b>	L4

## Load capacity (Kg)

km/h / bar	10.00
10	10500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/9/2024 5:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..