

ROCK STAR IND4 - Technical Specifications



Description

ROCK STAR PORT IND-4 has been specifically designed for empty container handlers and forklifts. In addition to excellent traction, the unique tread compound provides superior cut and chip resistance. ROCK STAR PORT IND-4 ensures outstanding load capacity and extraordinary durability.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Empty Container Handler • Forklift

| Version | PORT INDUSTRIAL |
|-----------|-----------------|
| Туре | TL |
| Tyre Size | 14.00 - 24 |

Dimensions International Standard

| Ply Rating | 28 |
|----------------------------|---------|
| Overall Width (mm) | 390 |
| Overall Diameter (mm) | 1425 |
| Static Loaded Radius (mm) | 635 |
| Rolling Circumference (mm) | 4350 |
| Rim Rec | 10.00 W |
| TRA Code | IND4 |

Load capacity (Kg)

| km/h / bar | 10.00 |
|------------|-------|
| 10 | 13500 |
| | |

Printed on 4/27/2024 7:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..