

## RT 857 - Technical Specifications



### Description

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	420/85 R 26 (16.9 R 26)
LI/SS	138 A8/B

## Dimensions US Standard

Usa code	94045013
Section Width (inch)	17.2
Overall Diameter (inch)	54.1
Static Loaded Radius (inch)	24.3
Rolling Circumference (inch)	162
Rim Rec	DW 15 L
Rim Alt	W 14 L ; W 15 L ; W 16 L ; DW 16 L
ECE	E11-106R-003471
TRA Code	R1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2870	3340	3800	4280	4740	5200
25	2870	3340	3800	4280	4740	5200
20	3080	3570	4080	4570	5080	5580
5 LT	3850	4480	5100	5730	6360	6980
5 HT	3080	3570	4080	4570	5080	5580

Printed on 12/8/2023 4:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..