

SKID POWER HD (A) - Technical Specifications

Description

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer



| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 18 X 8.5 - 8 |
| LI/SS | 97 A2 |

Dimensions US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94030422 |
| Ply Rating | 8 |
| Section Width (inch) | 8.3 |
| Overall Diameter (inch) | 18.1 |
| Static Loaded Radius (inch) | 8.1 |
| Rolling Circumference (inch) | 53.4 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |
| ECE | E11-106R-005559 |

Load capacity (lbs)

| mph / psi | 44 |
|-----------|------|
| 5 | 1630 |
| 10 | 1290 |
| 15 | 1190 |

Printed on 5/6/2024 10:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..