

## SKID POWER HD (A) - Technical Specifications



### Description

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Industrial: Skid Steer

Version	IMPLEMENT
Type	TL
Tyre Size	26 X 12 - 12
LI/SS	114 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	305
Overall Diameter (mm)	660
Static Loaded Radius (mm)	297
Rolling Circumference (mm)	1947
Rim Rec	10.50 I - 55
Rim Alt	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA
ECE	E11-106R-003538

Load capacity (Kg)

km/h / bar	5.40
40	1180

Printed on 5/6/2024 10:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..