

SNOW - RIDE (A) - Data Sheet



Description

SNOW-RIDE is particularly suitable for municipality and maintenance applications in winter conditions with compact loaders and skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks and ensures a longer tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Compact Loader

Industrial: Skid Steer

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
12.5/70 - 16	STANDARD	10	10 LB		315	850	385	2550	TL	1	
12.5/70 - 16	STANDARD	6	10 LB		315	850	385	2550	TL	1	
10 - 16.5	STANDARD	10	8.25		270	780	357	2340	TL		
10 - 16.5	STANDARD	6	8.25		270	780	357	2340	TL		
12 - 16.5	STANDARD	6	9.75	-	305	835	379	2505	TL		
12 - 16.5	STANDARD	10	9.75	-	305	835	379	2505	TL		
15.5/60 - 18	STANDARD	10	W 13		395	938	425	2814	TL	1	'E11-106R-005302
17.5/65 - 20	STANDARD	10	W 14 L		445	1095	493	3285	TL		

Printed on 4/27/2024 7:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..