

STEER FARM - Technical Specifications



Description

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: 2WD Tractor

Version	STANDARD
Type	TT
Tyre Size	5.20 - 14
LI/SS	75 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	135
Overall Diameter (mm)	625
Static Loaded Radius (mm)	296
Rolling Circumference (mm)	1837
Rim Rec	3.50 D
Rim Alt	4.00 E
ECE	E11-106R-004092
TRA Code	F2

Load capacity (Kg)

km/h / bar	4.50
30	387

Printed on 5/5/2024 11:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..