

TF 8181 - Technical Specifications



Description

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.

UM

International Standard

Construction



Machinery

Agriculture: 2WD Tractor

Industrial: Trailer

Version	SPECIAL
Туре	ТТ
Tyre Size	7.50 - 18
LI/SS	106 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	208
Overall Diameter (mm)	875
Static Loaded Radius (mm)	410
Rolling Circumference (mm)	2605
Rim Rec	5.50 F
ECE	E11-106R-005254
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	950

Printed on 4/28/2024 9:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..