

TR 117 - Technical Specifications



Description

TR 117 is ideal for irrigation applications with pivot irrigators. Its specially designed tread pattern provides excellent traction and outstanding self-cleaning properties.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Pivot Irrigator

Version	STANDARD
Type	TL
Tyre Size	11.2 - 24
LI/SS	98 A8

Dimensions US Standard

Usa code	94029044
Ply Rating	4
Section Width (inch)	11.2
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	20
Rolling Circumference (inch)	126.2
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-001966
TRA Code	R1

Load capacity (lbs)

mph / psi	18	22
25	1650	---
CREEP	---	3495

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/6/2024 3:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..