

TR 135 - Technical Specifications



Description

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor
Industrial: Trailer

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	155 A8

Dimensions US Standard

Usa code	94028009
Ply Rating	16
Section Width (inch)	23.1
Overall Diameter (inch)	62.4
Static Loaded Radius (inch)	27.6
Rolling Circumference (inch)	181.7
Rim Rec	DW 20 B ; DW 20 A
ECE	E11-106R-004598
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	8540

Printed on 4/23/2024 1:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..