



TR 144 - Data Sheet



Description

TR 144 is suitable to equip small tractors to be used in soil tillage operations. TR 144 ensures outstanding performance in all operating conditions which require excellent traction with high loads. It is also available in a "special" version, which is best suitable for heavy-duty service.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Small Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
7 - 16	STANDARD	R1	75 A6	4	6 L ; 6 LB ; 6.00 F		183	740	344	2223	TT		E4-106R-002205
7 - 16	STANDARD	R1	75 A6	4	6 L ; 6 LB ; 6.00 F		183	740	344	2223	TL		E4-106R-002205
7 - 16	STANDARD	R1	84 A6	6	6 L ; 6 LB ; 6.00 F		183	740	347	2253	TT		E11-106R-004322
8 - 16	HD	R1	91 A6	6	6 L ; 6 LB ; 6.00 F		200	785	358	2342	TT	1	E11-106R-004087
8 - 16	SPECIAL	R1	91 A6	6	6 L ; 6 LB ; 6.00 F		200	785	358	2342	TT		E11-106R-004324
8 - 16	STANDARD	R1	83 A6	4	6 L ; 6 LB ; 6.00 F		200	785	358	2342	TT		E11-106R-004323
8 - 16	STANDARD	R1	91 A6	6	6 L ; 6 LB ; 6.00 F		200	785	358	2342	TT		E11-106R-003483
8 - 16	STANDARD	R1	91 A6	6	6 L ; 6 LB ; 6.00 F		200	785	358	2342	TL		E11-106R-003483
8 - 16	STANDARD	R1	98 A6	8	6 L ; 6 LB ; 6.00 F		200	785	358	2342	TT		E11-106R-004325
9.5 - 16	STANDARD	R1	96 A6	6	W 8 L	8 LB	245	850	388	2558	TT		E4-106R-002643
9.5 - 16	STANDARD	R1	102 A6	8	W 8 L	8 LB	245	850	388	2558	TT		E11-106R-004327
9.5 - 16	STANDARD	R1	96 A6	6	W 8 L	8 LB	245	850	388	2558	TL		E4-106R-002643
9.5 - 16	STANDARD	R1	102 A6	8	W 8 L	8 LB	245	850	388	2558	TL		E11-106R-004327
8 - 18	SPECIAL	R1	94 A6	6	W 6	W 7 ; 5.50 F	195	835	391	2535	TT		E11-106R-003496
8 - 18	SPECIAL	R1	100 A6	8	W 6	W 7 ; 5.50 F	195	835	391	2535	TT		E11-106R-006166
8 - 18	STANDARD	R1	85 A6	4	W 6	W 7 ; 5.50 F	195	835	385	2509	TT		E11-106R-004328
8 - 18	STANDARD	R1	94 A6	6	W 6	W 7 ; 5.50 F	195	835	385	2509	TT		E11-106R-006467
8 - 18	STANDARD	R1	100 A6	8	W 6	W 7 ; 5.50 F	195	835	385	2509	TT		E11-106R-006166
8.3 - 20	HD	R1	96 A6	6	W 7	W 6	211	890	414	2670	TT	1	E11-106R-004101
8.3 - 20	STANDARD	R1	96 A6	6	W 7	W 6	211	890	414	2670	TT	0	E11-106R-003484
9.5 - 22	STANDARD	R1	104 A6	6	W 8	W 7	235	1000	464	3008	TT		E11-106R-003485

Printed on 4/19/2024 3:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..