

## TR 317 - Technical Specifications

### Description

TR 317 is suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The TR 317 tire has a large contact area which provides excellent grip and outstanding stability in any condition along with great self-cleaning properties.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Orchard Harvester •  
Trencher



Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 8

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	215
Overall Diameter (mm)	450
Static Loaded Radius (mm)	198
Rolling Circumference (mm)	1305
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003495

## Load capacity (Kg)

km/h / bar	1.50
15	375

Printed on 5/3/2024 7:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..