

TR 393 - Technical Specifications



Description

TR 393 has been specially designed for hay balers, spreaders and implement machinery on and off the road. The special tread design provides best flotation and self-cleaning properties in addition to a long service life. Thanks to its large contact area, TR 393 ensures excellent traction and minimizes soil compaction.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Spreader

Version	STANDARD
Type	TL
Tyre Size	16.5L - 16.1 SL
LI/SS	128 B

Dimensions US Standard

Usa code	94053261
Ply Rating	6
Section Width (inch)	16.5
Overall Diameter (inch)	40.4
Static Loaded Radius (inch)	18.1
Rolling Circumference (inch)	116.8
Rim Rec	W14C
Rim Alt	W14CH
TRA Code	I2

Load capacity (lbs)

mph / psi	24
30	3960

Printed on 3/4/2024 11:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..