

## TR 882 - Technical Specifications



### Description

TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery  
• Trailer  
Industrial: Trailer

Version	HD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	875
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2605
SRI (mm)	410
Rim Rec	AG 13.00
ECE	E4-106R-001879

Load capacity (Kg)

km/h / bar	3.60
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2800
25 DW	2380
30 DW	2240
40 DW	2000

Printed on 4/28/2024 2:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..