

## TRAC GRADER + - Technical Specifications



### Description

TRAC GRADER + (G-2) is a bias-ply tire for graders. It is an excellent choice for the budget-minded customers. The durable casing is designed to last. The self-cleaning tread design shows open lug-to-void-ratio which provides best traction in all conditions. Its "special" version is made of a special cut-and-chip-resistant compound.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Grader

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	340
Overall Diameter (mm)	1280
Static Loaded Radius (mm)	600
Rolling Circumference (mm)	3943
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2

## Load capacity (Kg)

km/h / bar	4.00
40	3240

Printed on 4/25/2024 9:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..