

TRAC MASTER - Technical Specifications



Description

TRAC MASTER is a soil tillage and lawn and garden tire, suitable for small tractors and implement machinery. Its tread design provides excellent field protection along with great traction in the fields and optimum self-cleaning properties.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Implement Machinery • Small Tractor

Version	STANDARD
Type	TL
Tyre Size	380/50 - 15
LI/SS	116 B

Dimensions International Standard

Ply Rating	8
Section Width (mm)	380
Overall Diameter (mm)	780
Rim Rec	13 LB
ECE	E11-106R-008808

Load capacity (Kg)

km/h / bar	3.10
50	1250

Printed on 5/2/2024 7:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..