

XL GRIP (T) - Technical Specifications



Description

XL GRIP (E-3) best suits on/off trucks carrying heavy loads in mining applications. Its tread compound is designed to minimize cuts and punctures on harshest ground conditions. XL GRIP (E-3) offers exceptional traction and provides an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

OTR: On/Off Truck

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	320
Overall Diameter (mm)	1155
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3465
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.60
90 LS/LD	3450

Printed on 5/3/2024 4:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..