

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/65 R 28
LI/SS	135 D/138 A8

Dimensions US Standard

Usa code	94052394
Section Width (inch)	16.5
Overall Diameter (inch)	49.5
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	150.6
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-002974
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	2260	2600	2990	3370	3760	4130	4480	4810
30	2380	2730	3130	3540	3950	4340	4700	5050
25	2450	2810	3230	3650	4070	4480	4840	5200
20	2600	3000	3440	3880	4320	4760	5150	5530
5 LT	3030	3480	4000	4520	5040	5560	6010	6450
5 HT	2600	3000	3440	3880	4320	4760	5150	5530

Printed on 27/01/2021 09:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..